
MSDS SHEETS
FOR ORDER: 57495

SHIP-TO ADDRESS INFORMATION

: CLEAN AIR INSTRUMENT RENTAL
: 500 WEST WOOD STREET
: PALATINE IL 60067

LINE NUMBER : 005
PRODUCT CODE : 0502C300076RAL
DESCRIPTION : CARBON DIOXIDE, OXYGEN IN N2

AIR LIQUIDE AMERICA SPECIALTY GASES LLC

SUPPLIER ADDRESS: 1290 COMBERMERE STREET

TROY, MI 48083

EMERGENCY PHONE: (248) 589-2950
NUMBER

1. CHEMICAL PRODUCT

PRODUCT NAME: CARBON DIOXIDE, OXYGEN IN N2

SYNONYMS: NONE

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredient Name	Formula	CAS#	Concentration	Exposure Limits (PPM)			
				ACGIH TLV	OSHA PEL	MAC	Other STEL
Carbon Dioxide	CO2	124-38-9	5-50 PCT	5000	5000	5000	30000
Oxygen	O2	7782-44-7	20-23.5 PCT	NE	NE	NE	NE
Nitrogen	N2	7727-37-9	balance	S/A	S/A	S/A	S/A

Note: S/A = SIMPLE ASPHYXIANT NE = NONE ESTABLISHED

3. HAZARD IDENTIFICATION

*** EMERGENCY OVERVIEW ***
High pressure oxidizing gas.
Vigorously accelerates combustion.

POTENTIAL HEALTH EFFECTS

ROUTES OF ENTRY: Inhalation

ACUTE EFFECTS: Exposure to carbon dioxide at 1-4% concentrations results in increased respiratory volume. Concentrations greater than 4% produce labored breathing and is dangerous for even a few mixtures. Extended exposure to oxygen at higher pressure maybe hazardous. A variety of central nervous system effects may result from breathing oxygen greater than 2 atm. Symptoms include dizziness, impaired coordination, visual and hearing disturbances and seizures. Mixture can act as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPOSURE: None

CARCINOGENITY (US Only):

NTP – No

IARC – No

OSHA REGULATED – No

4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: None

SKIN CONTACT: None

AIR LIQUIDE AMERICA SPECIALTY GASES LLC

INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap

FLAMMABLE LIMITS: Nonflammable

Lower:

Upper:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions. Escaping gas mixtures containing more than 23% oxygen will accelerate the combustion of surrounding materials.

6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: None

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders. Use only oxygen cleaned equipment. Avoid oils and greases. Oxygen reacts violently with hydrocarbons particularly at high pressure.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well-ventilated areas. Keep valve protection caps on cylinders when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain concentration below flammable limits and to avoid asphyxiation.

PERSONAL PROTECTION

EYE/FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless
ODOR: Odorless.
PHYSICAL STATE: Gas
VAPOR PRESSURE: N/Ap
BOILING POINT: N/Ap
SPECIFIC GRAVITY: Gas
EVAPORATION RATE: N/Ap
ODOR THRESHOLD: None

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Flammable and combustible materials, especially greases and oils. Nitrogen reacts with Li, Nd and Ti at high temperatures. Carbon Dioxide being weakly acidic, reacts with alkaline materials to form carbonates and bicarbonates.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Toxic carbon monoxide when heated above 1700 deg. C.

11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return the cylinders to the supplier with any valve outlet plugs or caps secured and valve protection caps in place.

14. TRANSPORT INFORMATION

CONCENTRATION:

DOT DESCRIPTION (US ONLY):

PROPER SHIPPING NAME: Compressed gas, N.O.S.

HAZARD CLASS: 2.2 (Nonflammable)

IDENTIFICATION NUMBER: UN1956

REPORTABLE QUANTITIES: None

LABELING: Nonflammable Gas

ADR / RID (EU Only): Class2, 1A, 10

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well-ventilated truck.

15. REGULATORY INFORMATION

OSHA: Process Safety Management: Minor component is listed in appendix A 29 CFR 1910.119 as a highly hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity is 10,000 lbs.

EU NUMBER: N/Av

NUMBER IN ANNEX 1 OF DIR 67/548: Mixture is listed in annex 1.

EU CLASSIFICATION: N/Av

R: 20

S: 9, 17, 39

16. OTHER INFORMATION

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a gas cylinder, which has not been filled by the owner or with his written consent, is a violation of federal law (49 CFR).

ABBREVIATIONS:

N/Av – Not Applicable

N/Av – Not Available

SA – Simple Asphyxiant

NE – None Established

Disclaimer: Information included in this document is given to the best of our knowledge, however, no warranty is made that the information is accurate or complete. We do not accept any responsibility for damages by the use of the document.